

Fresh Air Supply Unit Quick Install Kit Fitting Guide

Sigrist Design Fresh Air Supply Unit's (FASU) can be supplied with an optional Quick Install Kit. The Quick Install Kit removes the need to independently flash the Fresh Air Unit to the building substrate. This enables expedited job processing, by significantly reducing the total amount of time required to completely install of the Sigrist Design Fresh Air Unit. The below guide illustrates how to install the Sigrist Design Quick Install Kit. All work should be completed whilst the room is vacant, and all electrical equipment and potential energy sources isolated prior to beginning. Work to site specific conditions and policy. All FASU units installed as per the relevant standards and guides, will be eligible for the standard warranty period and conditions.

Step Number	Step Photo/Description	Details
<p>1</p>	<p>Kit List-</p> <ul style="list-style-type: none"> <input type="checkbox"/> Tick - 1 X FASU Quick Install Flange <input type="checkbox"/> Tick - 4 X White Tek Screws <p>Tool List-</p> <ul style="list-style-type: none"> <input type="checkbox"/> Tick - 1 X Tek Screw Driver Bit <input type="checkbox"/> Tick - 1 X Impact Driver <input type="checkbox"/> Tick - 1 X White Silicone or Sealant <input type="checkbox"/> Tick - 1 X Caulking Gun 	<p>Check that kit contains the follow parts.</p> <p>Check that tools required are easily accessible.</p> <p>Ensure all relevant safety and processes or site policy are followed and complied with.</p>
<p>2</p>	<p>Fit Quick Install Kit as per the below diagram and seal edges with white sealant. Wall cut out for flange is 439mm x 439mm.</p> 	